

Features

- Heavy duty lifting power 1000N
- Opens door up to 20.5m²
- Built in energy friendly LED lighting system
- Auto reverse safety system
- 24V DC output for external accessories
- Auto close feature available when photo eye safety beams are installed
- Soft open and soft close feature

4DR1 v1 comes in a compact design suitable for single or double roller doors up to 20.5m².

To ensure safe and smooth operation the 4DR1 v1 comprises intelligent door profiling combined with a multi point obstruction detection algorithm to serve various door conditions.

The reliable and precision controlled 24V DC motor is engineered for smooth and quiet operation using the latest soft open/soft close feature. The 4DR1 v1 opener is well suited to the modern home owner looking for the latest in design and technology.

Door Type		
Max. Door Size	20.5m ²	
Max. Door Weight	80kg (Spring balanced)	
Max. Door Height	4.6m	
Door Travel limits	Max 4.5 turns of door drum approx.	



ΕI				_ 1
	Δc	4	-16	-
	$-\iota$. LI	-10-	

Input	AC 220~240V 50/60Hz
Max. Current	2A
Power	100W
Motor Type	24V DC
Standby power	2W

ж	

Max. Lifting Force	60kg
Rated Lifting Force	40kg
Max. Capacity	1000N

Transmitter

Frequency	433MHz
Operation Range	20 - 25 metres
Transmitter Capacity	20

Courtesy Light

Light Source	6 x Ultra Bright LEDs	
Lighting Time	2.5 minutes	

Warranty: 5 year motor - 2 year electronics