

THERE'S SO MUCH MORE BEHIND A  DOOR



Opener Comparison

STANDARD FEATURES

Feature	SECTIONAL, FLEX-A-DOOR AND TILTING DOORS		ROLLING DOORS	
	CAD S	GDO-11	GDO-6	CAD DIAMOND PD
Pulling force	700N	650N	450N	550N
Motor	DC	DC	DC	DC
Automatic force sensing	✓	✓	✓	✓
Soft start / soft stop	✓	✓	✓	✓
Standby power consumption	2.2W	2.2W	2.2W	2.0W
Drive	Chain	Chain		
Rail system	Steel C-Rail	Steel C-Rail		
Maximum recommended door size (area)	16.5m ²	13.5m ²	16.5m ²	16.5m ²
Courtesy light	Festoon globe	Festoon globe	Festoon globe	2 LED Modules
Courtesy light time	3 minutes	3 minutes	3 minutes	4 minutes
Operating frequency	Tri-Tran™ technology. UHF multi frequency FM	TrioCode™ multi frequency	TrioCode™ multi frequency	Tri-Tran™ technology. UHF multi frequency FM
Receiver type	Multi channel frequency hopping	Multi channel frequency hopping	Multi channel frequency hopping	Multi channel frequency hopping
Two button transmitter	✓ x 1	✓ x 1		
4 button keyring transmitter	✓ x 1	✓ x 1	✓ x 2	✓ x 2
Wall push button	✓	✓		
Memory registers	8	8	14	14
Warranty	5 year / 10,000 cycles	2 year / 5,000 cycles	2 year / 5,000 cycles	5 year / 10,000 cycles



Doors & Openers®

THERE'S SO MUCH MORE BEHIND A B&D DOOR

Call **13 62 63** or visit www.bnd.com.au for further information