STANDARD RANGE



The B&D Roll-A-Shutter[®] Standard collection is suitable for a wide range of industrial and commercial requirements, and features a selection of shutters for virtually any application – from the largest building complexes, to small single factories and warehouses.

Decades of expertise and experience, together with access to high-level technical resources, allows B&D to design and provide the right product for virtually any need.

A continuous programme of research, development and testing has resulted in continual product improvements and ensures suitability, durability and – most importantly – economy.



PRE-COLOURED OR GALVANISED SLATS STEEL CURTAIN ALUMINIUM BOTTOM RAILS WEATHERSEALS NYLON END CLIPS MANUAL OR ELECTRIC

THERE'S SO MUCH MORE BEHIND A B&D DOOR



ROLL-A-SHUTTER STANDARD PRODUCT RANGE

ALL SHUTTERS IN THE ROLL-A-SHUTTER® STANDARD COLLECTION PROVIDE AN ARRAY OF FEATURES THAT ENSURE SUPERIOR PERFORMANCE, QUALITY AND DURABILITY.

6/100 (0.6 x 100MM)

Suited for all-round light industrial applications.

- Easily operated manually.
- Chain-geared or electrically powered.
- Suitable for openings requiring strong closure.
- The most widely used shutter across majority of applications.

8/100 (0.8 x 100MM)

Ideal for most general-purpose applications such as medium-size factory doorways etc.

 Operated by a choice of either manual, chain-geared or power-driven methods, ensuring minimal operational effort.

10/100 (1.0 x 100MM)

Designed for all sizes and types of industrial and commercial applications. Ideal for heavy-duty wind loading and large opening situations. Suitable for factories, warehouses, service stations etc.

• Custom built with chain or heavy-duty electric operation, ensuring minimal operational effort.





STANDARD FEATURES

WEATHERSEALS

All shutters are fitted with bottom rail weatherseals, which feature fins, to help prevent dust and leaves entering under the shutter.

BOTTOM RAILS

All shutters are equipped with aluminium bottom rails as standard.

NYLON END CLIPS

All shutters are fitted with specially-moulded nylon end-clips to ensure smooth, quiet, low-friction operation. Windlocked types are available as an option (refer to Options section).

GUIDES

Standard galvanised 70mm deep channel guides, cold roll formed from 2.0mm steel.

LOCKING

Standard locking is provided by a guide-mounted lockable chain clip for all electric and chain-operated shutters. For non chain-operated shutters, bottom rail Padbolt-type locking is supplied.

BRACKETS

Support brackets are fabricated from mild steel angle, supplied with spindle support angles and fitted with 12mm steel bolts.

DRUMS

Heavy duty steel drum and bracket assemblies for long, reliable product life.

GEARS

Chain-operated shutters are fitted with a spur gear attached to one end of the drum and meshing, with a number of gears providing desired gear ratio. Motor drive shutters are fitted with a sprocket to one end of the drum and driven by a transmission chain.

SPRINGS

Helical torsion-type springs made from spring steel wire conforming to AS1472. Designed to suit to opening dimensions, without exceeding the safe working stress limits.

ELECTRIC OPERATION

All shutters within the range can be electrically operated. A wide range of openers are available for all applications, from the most basic operation to fully automated. All openers include emergency, manual chain-operation in case of power failure.

FINISH

Red oxide painted drum and bracket finish, in addition to galvanised or pre-coloured curtain.

SPACE REQUIREMENTS

All products within the Roll-A-Shutter[®] Standard collection require specific headroom, sideroom and backroom allowances. Refer to the below table for allowances according to Roll-A-Shutter height range.

HEIGHT	HEADROOM	BACKROOM	DRIVE END SIDE ROOM		
			CHAIN OPERATION	ELECTRIC OPERATION	PLAIN END SIDE ROOM
2195 to 3195	540	390	240	460	200
3200 to 3795	570	420	250	470	210
3800 to 4895	600	450	250	470	210
4900 to 6000	630	476	250	470	210

ASK US ABOUT OUR OPTIONS

B&D have a range of options which complement the Roll-A-Shutter[®] Standard collection.

With a large selection of options including wind lock systems, mullions, slotted and perforated slats, and many others. B&D can deliver a door that best suits the requirements of your business. For more information on options please talk your B&D representative, or refer to our Roll-A-Shutter[®] Options brochure.

Roll-A-Shutter[®]

COLOUR AVAILABILITY

The B&D Roll-A-Shutter[®] Standard collection is currently available in a popular selection of pre-coloured or galvanised slats.

KEY COLOUR CHART



The colours shown in this guide are as close to the actual colours as the printing process allows and may vary from actual. Before making your final selection, please request an actual colour sample from your B&D representative.

YOUR B&D REPRESENTATIVE IS

B&D Doors has offices servicing all states. For more details on this product or our other ranges, phone **13 62 63** or visit **www.bnd.com.au**

Notes / Information

- a) The company reserves the right to make changes or improvements to the products or accessories without notice and without incurring any obligation to make similar changes or improvements to goods previously ordered. Specifications subject to change without notice.
- b) Prefixed trademarks are trademarks of B&D Australia Pty Ltd. Abuse of these trademarks will result in legal action.
- c) Details correct at date of publication.
- d) B&D Roll-A-Shutters are covered by a 1 year warranty for complete door and parts, conditional on proper care. Full details of the warranty are available, on request, from your nearest B&D office.

B&D Australia Pty Ltd ABN 25 010 473 971, an Alesco company. © 2009 B&D Australia. For more details on this product or our other ranges visit www.bnd.com.au



THERE'S SO MUCH MORE BEHIND A B&D DOOR

Call 13 62 63 or visit www.bnd.com.au for further information.